

KEY DIFFERENCES

	DELUXE SERIES	ECONOMY SERIES
Efficiency	>92%	>89%
Audible Noise	Noise Free, No Internal Fans	≤45 dBA at 1 meter from surface of unit
Output EMI Filter	150Khz - 30Mhz	NO
Moisture Sensitivity	Sealed Electronics	Internal Fan
External Cooling Fan Control	Auto on/off, controlled by heat sink temperature & load level	NO
Internal Cooling Fan	NO	Internal fan will run at low speed continuously when temperature inside is low and load is no more than 68%. When load level is over 70%, or when internal temperature is over 60° C, fan runs at full speed
Output Compatibility with UPS	NOT SUGGESTED	YES
Wall Mountable	YES	NO
Approvals and Safety Markings	CE UL-ULus (CCN: QQFU/7) Power Units Other Than Class 2, UL 1012, Seven Edition, October 14, 2008 UL-cUL: CAN/CSA-C22.2 No. 107.1-01, September, 2001 DEMKO-CB IEC60950-1:2005+A1:2009+A2:2013 (Ed. 2.2) TUV/SUD-CB IEC 60335-1:2010+A1:2013 (Ed. 5.1) FCC: CISPR22 AND Part15B ClassB RoHS Compliant Directive 2002/95/EC	CE